



Life Paint Company
 12927 Sunshine Ave
 Santa Fe Springs, CA 90670

MATERIAL SAFETY DATA SHEET

ACRYLIC FLOOR PAINT STONE GRAY

Page: 1
 1/26/2006

PRODUCT NAME: ACRYLIC FLOOR PAINT STONE GRAY
 PRODUCT CODE: 10-42/150

HMIS CODES: H F R P
 1 0 0 B

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: LIFE PAINT COMPANY
 ADDRESS : 12927 SUNSHINE AVENUE
 SANTA FE SPRINGS, CA 90670-0488

EMERGENCY PHONE : (800) 424-9300
 INFORMATION PHONE : (562) 944-6391

NAME OF PREPARER : MICHAEL DE LA VEGA DATE PRINTED : 1/26/2006

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE		WEIGHT
		mm Hg	@ TEMP	PERCENT
METHYL CARBITOL OSHA PEL: NE, ACGIH TLV: NE, OTHER: NE	111-77-3	.2	68	5
PROPYLENE GLYCOL MONOBUTYL ETHER OSHA PEL: NA, ACGIH TLV: NA	5131-66-8	.6	68	5

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

WARNING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR REPRODUCTIVE HARM MAY BE PRESENT IN THIS PRODUCT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.2
 VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than ether
 COATING V.O.C.: 1.61 lb/gl MATERIAL V.O.C.: 0.78 lb/gl
 SOLUBILITY IN WATER: DILUTABLE
 APPEARANCE AND ODOR: COLORED LIQUID WITH MILD ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 150 METHOD USED: N/A
 FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1 UPPER: 22.7

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES

IF WATER IS USED FOG NOZZLES ARE PREFERRED. USE WATER TO COOL CLOSED CONTAINERS

UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.



Life Paint Company
12927 Sunshine Ave
Santa Fe Springs, CA 90670

MATERIAL SAFETY DATA SHEET

ACRYLIC FLOOR PAINT STONE GRAY

Page: 2
1/26/2006

SECTION V - REACTIVITY DATA

STABILITY: STABLE

CONDITIONS TO AVOID

HIGH TEMPERATURES OR EXTREME HEAT

INCOMPATIBILITY (MATERIALS TO AVOID)

OXYGEN AND STRONG OXIDIZERS, SULFURIC ACID, AND OTHER DEHYDRATING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OVEREXPOSURE MAY CAUSE DIZZINESS, HEADACHES, EVEN UNCONSCIOUSNESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED SKIN CONTACT WILL CAUSE DRYING AND DEFATING OF SKIN TISSUE LEADING TO IRRITATION AND DERMATITIS. EYE CONTACT MAY CAUSE IRRITATION AND BLURRED VISION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DRYING AND DEFATTING OF SKIN

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTATION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING, AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

THE PROPER USE OF THIS PAINT PRODUCT DOES NOT PRESENT ANY SERIOUS HEALTH HAZARD KNOWN TO LIFE PAINT COMPANY.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:
No

N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN. INGESTION: INDUCE VOMITTING IF VICTIM IS CONSCIOUS. CALL PHYSICIAN IMMEDIATELY SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH EYES WITH WATER. CALL PHYSICIAN IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL IGNITION SOURCES. VENTILATE CONFINED SPACES. AVOID BREATHING VAPORS. RECOVER FREE LIQUID AND ABSORBENT MATERIAL



Life Paint Company
12927 Sunshine Ave
Santa Fe Springs, CA 90670

MATERIAL SAFETY DATA SHEET

ACRYLIC FLOOR PAINT STONE GRAY

Page: 3
1/26/2006

FROM SPILL ARE. KEEP OUT OF SEWERS AND WATERWAYS.

WASTE DISPOSAL METHOD

DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, OR UNDERGROUND WATER SUPPLIES. INCINERATE OR BURY IN AN APPROVED LANDFILL. BE CERTAIN TO COMPLY WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS IN THE WASTE DISPOSAL METHOD THAT YOU CHOOSE.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, OPEN FLAME, OR STRONG OXIDANTS. USE ONLY IN WELL VENTILATED AREAS. AVOID BREATHING VAPORS. AVOID CONTACT WITH SKIN. KEEP OUT OF THE REACH OF CHILDREN.

OTHER PRECAUTIONS

N/A

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION

USE APPROPRIATE NIOSH APPROVED RESPIRATORY EQUIPMENT WHEN OCCUPATIONAL EXPOSURE LIMITS ARE EXCEEDED.

VENTILATION

LOCAL EXHAUST AND MECHANICAL VENTILATION ARE RECOMMENDED.

PROTECTIVE GLOVES

NEOPRENE OR NON SOLUBLE PLASTIC.

EYE PROTECTION

GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

N/A

WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING OR SMOKING.

SECTION IX - DISCLAIMER

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT SOURCES BELIEVED BY LIFE PAINT CORPORATION TO BE ACCURATE. LIFE PAINT CORPORATION DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THE INFORMATION SUPPLIED HERE.