



# LIFE™

## Product Specifications

### **PRO COAT "08" Series Semi-Gloss Wall & Trim**

**Product Description:**

A Semi-gloss enamel for use in service areas where a high degree of washability is expected.

**Finish:** Semi-Gloss

**Recommended Surfaces:**

Interior-Exterior

- ✓Wood
- ✓Wallboard
- ✓Kitchens
- ✓Masonite
- ✓Baths
- ✓Metal

**Package Size:** Gallons, 5 Gallons

**Color:**

- 00 Hi Hide White
- 16 Swiss Coffee
- 19 Classic Navajo White

**Surface Preparation:** All surfaces must be free of dirt, oil, soot, loose and peeling paint, excessive paint chalk or other contaminants. A thorough washing with a T.S.P. solution is recommended to remove these contaminants. Rinse completely with clear water. Remove all wallpaper and all glue before painting. Patch all holes with spackle and sand smooth. Spot prime all patched areas.

**Glossy Surfaces:** For adhesion and ease of application, glossy surfaces must be flattened by sanding or by using a flat acrylic or oil based primer. Latex base or water base products will not adhere well to glossy surfaces. See "SURFACE PREPARATION."



**Unpainted Surfaces:** Prime all unpainted drywall and wood surfaces with primer.

**Surfaces:** Remove all chalk, loose, flaking, or peeling paint and remove efflorescence.

**Mildew:** DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. See precautions on bleach label for handling before using.

**Water Stains:** Block all water stains with Life's 3300 Stain Killer Primer.

**CAUTION:** Apply at temperatures above 500F.

**Application:**

Brush, roller, or spray.

**CAUTION:** Do not apply when temperatures are below 50°F or is expected to drop below 40°F, within a 24 hour period or, when painting exterior surfaces, when fog or rain is in the 24 hour forecast.

**Drying Time:** Dries in 2 hours. Can recoat in 4 hours.

**Thinning:** If necessary, a small amount of water, but do not over thin.

**Clean-up:** Clean tools and hands with warm soapy water and rinse thoroughly.

**Technical Information**

**Type:** Vinyl Acrylic  
**Diluent:** Water  
**Solids Content:** 46-49% by weight  
31-34% by volume

**Viscosity:** 89 KREBS units at 77°F  
**Flash Point:** >200°F  
**Maximum V.O.C.:** 50 grams per liter

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V. O.C. of this product does not exceed 50 grams/liter. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).  
**KEEP FROM FREEZING**