



LIFE™

Product Specifications

49 Series 100% Acrylic Ceramic Satin Enamel

Description: A premium quality 100% Acrylic "Ceramic" finish. This product contains unique "micro-ceramic" technology that allows most household stains to be easily wiped away with warm soap and water. It is formulated for excellent hide, touch-up, and ease of application and provides superior durability and years of trouble-free protection.

Use:

Exterior - Trim, Wood, Metal
Interior - Walls, Wallboard, Metal, Wood

Advantages

- ✓ Superior flow and leveling
- ✓ One coat coverage (see below)
- ✓ Excellent adhesion to glossy surfaces
- ✓ Superior stain & abrasion resistance

Finish: Satin Enamel


Package Size: Quart, Gallon and 5 Gallon

Color:

-00 Hi Hide White	-61 New Navajo White
-66 Swiss Coffee	-95 Deep Base
-98 Accent Base	-90 Tint Base

Surface Preparation: All surfaces must be free of dirt, oil, soot, excessive paint chalk or other contaminants. A thorough washing with a T.S.P. solution is recommended to remove these contaminants. Rinse completely with clear water. Remove all wallpaper and all glue before painting. Patch all holes with spackle and sand smooth. Spot prime all patched areas with Life's 7075 or 3300 Acrylic Primer.

Mildew: DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. See precautions on bleach label for handling before using. Acrylic "ceramic" coatings contains E.P.A. antimicrobial registered mildewcide to protect the paint film. All mold, mildew, and fungi must be completely and thoroughly removed before painting all substrates.



Unpainted Surfaces:

Clean all surfaces. (See "Surface Preparation"). Prime all surfaces with Life's 7075 or 3300 Acrylic Primer. New plaster must cure for at least 30 days before priming and finishing.

Previously Painted Surfaces:

Clean all surfaces. (See "Surface Preparation"). Remove all loose and peeling paint.

Glossy Surfaces: All glossy surfaces should be dulled by sanding or by the use of a "liquid sandpaper" and/or primed with Life's 7075 or 3300 Acrylic Primer.

Water Stains: Block out all water stains with Life's 7075 Primer before applying your finish coat.

Metal: Metal must be free of rust. Clean and etch all new metal. Prime all bare metal with Life's 7075 or 3300 Acrylic Primer.

Application: Apply at temperatures above 55°F. Stir thoroughly. Apply with a good quality 1/4" to 3/8" all purpose nap roller. Can be brushed, rolled or sprayed. Do not apply late in the day or when dew, rain, fog or mist is likely, since moisture can damage the fresh paint film.

Coverage: Apply two coats for maximum durability. Coverage of 300 to 400 sq. ft. per gallon on smooth surfaces and 150 to 300 sq. ft. per gallon on rough, textured or porous surfaces. When more than one container of the same color is used on a job, it is recommended that these containers be blended together to insure a uniform color throughout the job.

One Coat Coverage: Life Paint uses the finest pure color pigments available to achieve unequaled color hue and brightness. For this reason some colors may require more than one coat to attain uniform coverage. Deep tone and accent colors by their nature contain very small amounts of opaque white pigments and may generally require 2 to 4 coats for complete coverage.

Thinning: We do not recommend thinning. If spraying, a small amount of water can be added.

Drying Time: Dries to touch in 1 hour. Can recoat in 8 hours. Do not scrub the new coating for 7 days.

Clean-up: Clean tools and hands with warm soapy water and rinse thoroughly.

CAUTION: Do not apply when temperatures are below 50°F or is expected to drop below 40°F within a 24 hour period or, when painting exterior, when fog or rain is in the 24 hour forecast.

WARRANTY: When the warranted product is applied in accordance with label instructions and common sense widely accepted painting practice and procedures, Life Paint will warrant said product against manufacturing defects that might cause premature failure such as blistering, peeling, or unusual wear for as long as the homeowner owns the home where the product was applied. This warranty extends only to the owner of the single-family home to which the paint was applied during such owner's occupancy of such dwelling. In the event of a warranted failure and upon the presentation of proof of purchase the remedy will be the provision price for said product. This warranty does not include labor or the costs associated with labor. This LIFETIME LIMITED WARRANTY may not be transferred or assigned and extends specific legal rights which may vary from state-to-state.

Technical Information

Type:	Urethane Modified Acrylic	Viscosity:	KREBS units at 77°F
Diluent:	Water	Flash Point:	200°F
Solids Content:	44-47 % by weight 32-35 % by volume	Maximum V.O.C.:	50 grams per liter

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V.O.C. of this product does not exceed 50 grams/liter. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.