



LIFE™

Product Specifications

Super-Pro Premium "51" Series Latex Flat Wall

Product Description: Life's 51 Series is a Flat Latex Wall Paint that will cover most surfaces in one coat. Darker colors may require additional coats.

Finish: Flat

Recommended Surfaces: Interior-Exterior

* Concrete * Stucco * Wallboard * Masonry

Drying Time : Dries to touch in 1 hour. Allow 4 hours drying time between coats.

Clean-Up: Clean hands and tools with warm soapy water and rinse thoroughly.

Thinning: Thinning is not recommended. If spraying, a small amount of water may be added.

Coverage: Apply two coats for maximum durability. Coverage is 300 to 400 sq. ft. per gallon on smooth surfaces and 150 to 300 sq. ft. per gallon on rough, textured or porous surfaces. When more than one container of the same color is used on a job, it is recommended that these containers be blended together to insure a uniform color throughout the job.

Application: Apply at temperatures above 50°F but not in extreme heat. Stir thoroughly before use. May be brushed, rolled or sprayed. Do not apply late in the day or when dew, rain, fog or mist is likely, since moisture can damage the fresh paint film.



Surface Preparation : All surfaces must be free of dirt, oil, soot, loose and peeling paint, excessive paint chalk or other contaminants. A thorough washing with a T.S.P. solution is recommended to remove these contaminants. Rinse completely with clear water. Remove all wallpaper and all glue before painting. Patch all holes with spackle and sand smooth.

Glossy Surfaces : All glossy surfaces should be dulled by sanding and then primed with Life's 7075 Primer.

Unpainted Surfaces: Clean all surfaces. (See "Surface Preparation") Prime all wood surfaces with Life's 7075 Primer. Prime all drywall with Life's 4650 Sealer.

Stucco Surfaces: Remove all chalk, loose, flaking, or peeling paint and remove efflorescence.

Mildew : DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. See precautions on bleach label for handling before using.

Water Stains: Block all water stains with Life's 3300 Stain Killer Primer.

Metal: Metal must be free of rust. Clean and etch all new metal. Prime all bare metal with Life's 7075 Primer.

Touch Up : Touch up with a mixture of 8 parts "51" Series to 1 part water.

Technical Information

Type:	Vinyl Acrylic	Viscosity:	100-105 KREBS units at 77°F
Diluent:	Water	Flash Point:	>250°F
Solids Content:	48-51% by weight 28-31% by volume	Maximum V.O.C.:	50 grams per liter

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. KEEP FROM FREEZING