



LIFE™

Product Specifications

PRO COAT "52" Series Semi-Gloss Wall & Trim

Product Description:

A "kid-proof" quality Acrylic Enamel for use in service areas where a high degree of washability is expected. The 52 Series will not yellow and will stay color fast for years. Darker colors may require additional coats.

Finish: Semi-Gloss

Recommended Surfaces:

Exterior - Trim, wood, metal
Interior - Walls, wallboard, metal, wood

Advantages:

- ✓Super scrubbable
- ✓Excellent stain resistance
- ✓Low sheen beauty for any room
- ✓Tintable to over 500 custom colors

Package Size: Gallons, 5 Gallons

Color:

-85 White & Pastel Base	-00 Hi Hide White
-13 Ant.White (Cottage)	-61 New Nav.White
-66 Swiss Coffee	-90 Tint Base
-95 Deep Base	-98 Accent Base

Surface Preparation:

All surfaces must be free of dirt, oil, soot, loose and peeling paint, excessive paint chalk or other contaminants. A thorough washing with a T.S.P. solution is recommended to remove these contaminants. Rinse completely with clear water. Remove all wallpaper and all glue before painting. Patch all holes with spackle and sand smooth. Spot prime all patched areas with Life's 7075 Primer.



Glossy Surfaces:

All glossy surfaces should be dulled by sanding and then primed with Life's 7075 Primer.

Exterior Wood:

Prime all bare wood surfaces with Life's 7075 Primer.

Unpainted Surfaces:

Clean all surfaces. (See "Surface Preparation") Prime all surfaces with Life's 7075 Primer.

Mildew:

DO NOT PAINT OVER MILDEW. Mildew is a fungus, brown, black, grey or even white in color, and will rapidly grow through any coating applied over it. A solution of 50% household bleach and 50% water will kill the mildew. Rinse thoroughly. See precautions on bleach label for handling before using.

Water Stains:

Block out all water stains with Life's 3300 Stain Killing Primer before applying your finish coat.

PRO COAT "52" Series

Semi-Gloss Wall & Trim

Metal:

Metal must be free of rust. Clean and etch all new metal. Prime all bare metal with Life's 7075 Primer.

Application:

Apply at temperatures Above 50°F. Stir thoroughly before use. May be brushed, rolled or sprayed. Do not apply late in the day or when dew, rain, fog or mist is likely, since moisture can damage the fresh paint film.

CAUTION

Do not apply when temperatures are below 50°F or is expected to drop below 40°F, within a 24 hour period or, when painting exterior surfaces, when fog or rain is in the 24 hour forecast.

Coverage

Apply two coats for maximum durability. Coverage of 300 to 400 sq. ft. per gallon on smooth surfaces and 150 to 300 sq. ft. per gallon on rough, textured or porous surfaces. When more than one container of the same color is used on a job, it is recommended that these containers be blended together to insure a uniform color throughout the job.

Drying Time

Dries to touch in 1 hour. Allow 4 hours drying time between coats.

Thinning

Thinning is not recommended. If spraying, thin with a small amount of water if necessary.

Clean-up

Clean tools and hands with warm soapy water and rinse thoroughly.

Technical Information

Type: Vinyl Acrylic
Diluent: Water
Solids Content: 36-39% by weight
24-27% by volume

Viscosity: 89 KREBS units at 77°F
Flash Point: >200°F
Maximum V.O.C.: 150 grams per liter

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V. O. C. of this product does not exceed 150 grams/liter. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.
KEEP FROM FREEZING